

# PAVING STONE SPECIFICATIONS

Western Interlock paving stones are made from a low moisture concrete mixture. They are made under high pressure and high frequency vibration, producing a very dense stone, low in water absorption (less than 5%) and with a high PSI rating (above 8000 psi). They are designed to meet or exceed ASTM 936 and ASTM C-67-73 (freeze/thaw) specifications.

<b>PAVING STONES</b>	<b>Pcs/ Layer</b>	<b>Layers/ Pallet</b>	<b>Pcs/ Pallet</b>	<b>Pcs/ Sq Ft</b>	<b>Sq Ft/ Layer</b>	<b>Sq Ft/ Pallet</b>	<b>Lbs/ Pcs</b>	<b>Lbs/ Sq Ft</b>	<b>Lbs/ Pallet</b>
Alpine Large Rectangle (70mm)	12	8	96	1.28	9.36	74.88	25	31.9	2400
Alpine Large Square (70mm)	9	8	72	.85	10.59	84.7	37.5	31.9	2700
Alpine Medium Square (70mm)	20	8	160	1.92	10.4	83.2	16.3	31.25	2600
Alpine Small Rectangle (70mm)	40	8	320	3.84	10.4	83.2	8.15	31.25	2600
Alpine Rotundo (sold as layer) (70mm)	12	4	48	NA	11.4	45.6	356	31.25	1425
Alpine Rotundo (single stones) (70mm)	12	8	96	1.04	11.5	92.3	30.1	31.25	2890
Arena Stone - Standard, Granite (60mm)	12	9	108	1	12	108	28	27.5	2970
Camino Large Rectangle (60mm)	25	10	250	2.42	10.3	103	11.36	27.5	2850
Camino Small Rectangle (60mm)	49	9	441	4.76	10.3	92.6	5.7	27.5	2514
Camino Square (60mm)	35	10	350	3.65	9.6	96	7.64	27.5	2680
City Square (60mm)	42	9	378	4.09	10.27	92.42	8	27.5	3024
Holland (60mm)	54	9	486	4.56	11.84	106.6	6.03	27.5	2931
La Lastra Large Square (50mm)	2	9	18	.25	8	72	94	24	1700
La Lastra Medium Square (50mm)	4	9	36	.45	9	81	54	24	1910
La Lastra Large Rectangle (50mm)	4	9	36	.34	12	108	71	24	2550
La Pietra Grande (60mm)	2	8	16	.33	6	48	84	27.5	1344
La Pietra - Quattro (sold by layer) (50mm)	10	8	80	NA	12	96	332	27.5	2656
Park - Cobble, Roka, Granite (60mm)	24	9	216	2.29	13.1	94.3	12.44	27.5	2593
Plaza - Cobble, Roka Granite (60mm)	18	8	144	1.53	10.45	94.1	17.97	27.5	2588
Rotundo (sold as layers) (60mm)	37	9	333	NA	11.5	103.5	316.67	27.5	2850
Slimline Cobble Rectangle (40mm)	30	12	360	3.24	9.26	111	5.6	18.15	2011
Slimline Cobble Square (70mm)	48	12	576	4.88	9.84	118	3.72	18.15	2143
Slimline Holland (40mm)	45	12	540	4.51	9.98	120	4	18.04	2160
<b>PERMEABLE STONES</b>	<b>Pcs/ Layer</b>	<b>Layers/ Pallet</b>	<b>Pcs/ Pallet</b>	<b>Pcs/ Sq Ft</b>	<b>Sq Ft/ Layer</b>	<b>Sq Ft/ Pallet</b>	<b>Lbs/ Pcs</b>	<b>Lbs/ Sq Ft</b>	<b>Lbs/ Pallet</b>
Permeare Holland Stone (60mm)	54	9	486	4.56	11.85	106.6	5.6	25.6	2750
Permeare Park Stone (60mm)	24	9	216	2.29	10.5	94.3	11.5	26.4	2500
Permeare Camino Square (60mm)	42	9	378	3.65	11.5	103.6	7.3	26.7	2770
Permeare Camino Rectangle (60mm)	30	9	270	2.42	12.4	111.5	10.9	26.4	2960
Turf Stone (100mm)	4	5	20	.385	10.4	52	72.8	28	1456
VS5™ Drain Pave (80mm)	20	6	120	2.29	8.66	52	16	37	1889