

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Basalite Fast Set Concrete, Basalite Rapid Post, 40,60,80,90# Concrete
 Product code : Not available

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Building and construction work

1.3. Details of the supplier of the safety data sheet

Basalite Concrete Products, LLC
 605 Industrial Way Dixon
 CA, 95620 - USA
 T 707-678-1901

1.4. Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Irritation 2
 Serious Eye Damage 1
 Skin Sensitization 1
 Carcinogenicity 1A
 Specific Target Organ Toxicity - Repeated Exposure 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. Causes damage to lungs through prolonged or repeated exposure.

Precautionary statements (GHS-US) :

Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available.

2.4. Unknown acute toxicity (GHS US)

4 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

Basalite Fast Set Concrete, Basalite Rapid Post, 40,60,80,90# Concrete

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable.

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Quartz	(CAS No) 14808-60-7	60 - 100	Carc. 1A STOT RE 1
Cement, portland, chemicals	(CAS No) 65997-15-1	4 - 13	Skin Irrit. 2 Eye Dam. 1 Skin Sens. 1 STOT SE 3
Disodium carbonate	(CAS No) 497-19-8	≤ 5	Eye Irrit. 2A

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.
- Symptoms/injuries after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns in the presence of moisture.
- Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Treat for surrounding material.
- Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and material for containment and cleaning up

- For containment : Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Basalite Fast Set Concrete, Basalite Rapid Post, 40,60,80,90# Concrete

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Methods for cleaning up : Vacuum or sweep material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Do not swallow. Avoid generating dust. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat, drink or smoke. Provide adequate ventilation. Do not use this product for abrasive blasting.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep container tightly closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
OSHA	OSHA TWA	(30)/(/%SiO ₂ + 2) mg/m ³ (total dust) (250)/(/%SiO ₂ + 5) mppcf (respirable fraction) (10)/(/%SiO ₂ + 2) mg/m ³ (respirable fraction)
Cement, portland, chemicals (65997-15-1)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) 50 mppcf (<1% Crystalline silica)
Disodium carbonate (497-19-8)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection : Wear suitable waterproof gloves.

Eye protection : Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Skin and body protection : Wear suitable waterproof protective clothing.

Respiratory protection : A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

Basalite Fast Set Concrete, Basalite Rapid Post, 40,60,80,90# Concrete

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: No data available
Color	: Various
Odor	: Odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not flammable
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapor pressure	: No data available
Relative density	: 2.6
Relative vapor density at 20 °C	: No data available
Solubility	: Insoluble
Partition coefficient: n-octanol/water	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Keep dry in storage.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Incompatible materials. Moisture.

10.5. Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

10.6. Hazardous decomposition products

None known.

Basalite Fast Set Concrete, Basalite Rapid Post, 40,60,80,90# Concrete

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified.

Basalite Fast Set Concrete, Basalite Rapid Post, 40,60,80,90# Concrete	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	No data available
LC50 inhalation rat	No data available

Disodium carbonate (497-19-8)	
LD50 oral rat	4090 mg/kg
LD50 dermal mouse	2210 mg/kg

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Based on available data, the classification criteria are not met.
Carcinogenicity : May cause cancer.

Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens

Reproductive toxicity : Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure) : Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure) : Causes damage to lungs through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.
Aspiration hazard : Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation : May cause respiratory tract irritation.
Symptoms/injuries after skin contact : Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.
Symptoms/injuries after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns in the presence of moisture.
Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Uncured cementitious materials or finely divided (crushed) concrete material is an environmental hazard, which may adversely affect fish and other wildlife. Do not use crushed concrete as fill near any aquatic habitat. Dispose of construction debris containing cement, including empty bags at a permitted landfill or by a disposal firm. Discharge of large quantities to any waterways would be expected to cause significant consequence on aquatic habitat. Do not use crushed concrete as fill near any aquatic habitat.

12.2. Persistence and degradability

Basalite Fast Set Concrete, Basalite Rapid Post, 40,60,80,90# Concrete	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Basalite Fast Set Concrete, Basalite Rapid Post, 40,60,80,90# Concrete	
Bioaccumulative potential	Not established.

Basalite Fast Set Concrete, Basalite Rapid Post, 40,60,80,90# Concrete

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

12.4. Mobility in soil

No additional information available.

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT.

Not regulated for transport.

Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. US State regulations

Basalite Fast Set Concrete, Basalite Rapid Post, 40,60,80,90# Concrete

State or local regulations	This product contains a chemical known to the State of California to cause cancer.
----------------------------	--

SECTION 16: Other information

Date of issue : 04/29/2015

Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.